(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 16 December 2004 (16.12.2004)

PCT

(10) International Publication Number WO 2004/107884 A2

(51) International Patent Classification7:

A23P

(21) International Application Number:

PCT/US2004/011493

(22) International Filing Date:

9 April 2004 (09.04.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 10/455,739

5 June 2003 (05.06.2003)

- (71) Applicant: FORMAX, INC. [US/US]; 9150 191st Street, Mokena, IL 60448 (US).
- (72) Inventors: LABRUNO, Ronald, F.; c/o Formax, Inc., 9150 191st Street, Mokena, IL 60448 (US). CONERTON, Douglas; c/o Formax, Inc., 9150 191st Street, Mokena, IL 60448 (US).
- (74) Agent: ERICKSON, Randall, T.; The Law Office of Randall T. Erickson, P.C., 425 W. Wesley St., Suite 1, Wheaton, IL 60187 (US).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS AND METHOD FOR FORMING TWO COMPONENT FOOD PRODUCT

(57) Abstract: A method and apparatus for forming molded food products having an outer first component and an inner second component is provided. The apparatus includes a pressurized supply of first component and a pressurized supply of second component. A mold housing extends along a first direction. A first end portion and a second end portion are arranged to be movable along the first direction within the mold housing and to be separated by a pre-selected distance along the first direction. An injector tube is in fluid communication with the supply of pressurized second component. The first and second end portions are arranged to be contained within the mold housing in a fill position to form a mold cavity within the mold housing around the injector tube. The mold cavity has an inlet in fluid communication with the supply of pressurized first component when in the fill position to receive first component to form a shell having an inside void. The injector tube provides a pathway for the pressurized second component into the inside void of the shell to fill the inside void with the second component to complete a two-component molded food product.

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 16 December 2004 (16.12.2004)

PCT

(10) International Publication Number WO 2004/107884 A3

(51) International Patent Classification7:

A23P 1/12

(21) International Application Number:

PCT/US2004/011493

(22) International Filing Date:

9 April 2004 (09.04.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 10/455,739

5 June 2003 (05.06.2003) US

- (71) Applicant: FORMAX, INC. [US/US]; 9150 191st Street, Mokena, IL 60448 (US).
- (72) Inventors: LABRUNO, Ronald, F.; c/o Formax, Inc., 9150 191st Street, Mokena, IL 60448 (US). CONERTON, Douglas; c/o Formax, Inc., 9150 191st Street, Mokena, IL 60448 (US).
- (74) Agent: ERICKSON, Randall, T.; The Law Office of Randall T. Erickson, P.C., 425 W. Wesley St., Suite 1, Wheaton, IL 60187 (US).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: APPARATUS AND METHOD FOR FORMING TWO COMPONENT FOOD PRODUCT



(57) Abstract: A method and apparatus (10) for forming molded food products having an outer first component (29) and an inner second component is provided. The apparatus (10) includes a pressurized supply of first component (29) and a pressurized supply of second component. A mold housing (31) extends along a first direction. A first end portion and a second end portion are arranged to be movable along the first direction within the mold housing (31) and to be separated by a pre-selected distance along the first direction. An injector tube (70) is in fluid communication with the supply of pressurized second component. The first and second end portions are arranged to be contained within the mold housing (31) in a fill position to form a mold cavity within the mold housing around the injector tube (70). The mold cavity has an inlet in fluid communication with the supply of pressurized first component (29) when in the fill position to receive first component (29) to form a shell having an inside void. The injector tube (70) provides a pathway for the pressurized second component into the inside void of the shell to fill the inside void with the second component to complete a two-component molded food product.

WO 2004/107884 A3



 before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(88) Date of publication of the international search report: 27 October 2005